

CERTAINTEED MACHINE WORKS

BOLT® 3

INSULATION BLOWING MACHINE



Lightning Fast Performance

Energize your installers with a portable, electric blow machine offering powerful performance, superior fiber conditioning, and the largest material hopper in its class.

The BOLT® 3 supercharges job completion times by easily moving all loosefill material types thru 150' of hose. Proper coverage in attics, walls, and cavities can be achieved lightning fast.

FEATURES & BENEFITS

- Patented Spiked Auger*
- Quad Agitation System
- Large 25 ft³ Hopper
- 3" Diameter Outlet
- Air-Only and Air-and-Material Functionality
- Material Slide Control
- 100' Remote Control Cord
- Built-in Hose Storage
- Fits Thru 36" Doorway
- Four Casters With 2 Rotating Lockable
- Welded Steel Construction
- Durable Powder Coat Finish
- Air Volume Control

SAFETY FEATURES

- **Emergency Stop** - Immediately shuts down power to the motor and blowers
- **Electrical Interlock** - Prevents machine operation if hopper is not in place
- **Hopper/Shelf Design** - Prevents access to rotating parts in the machine
- **Chain & Sprocket Guards** - Eliminates access to pinch points

MACHINE SPECIFICATIONS

| | |
|-----------------------|--|
| INSULATION | FIBER GLASS, STONE WOOL, CELLULOSE |
| POWER REQUIREMENTS | TWO 120V/15A CIRCUITS REQUIRED TWO 50' POWER CORDS PROVIDED |
| FIBERGLASS BLOW RATES | MAXIMUM: 18-19 LBS./MIN CONDITIONED: 14-15 LBS./MIN |
| CELLULOSE BLOW RATES | MAXIMUM: 31-32 LBS./MIN CONDITIONED: 24-25 LBS./MIN |
| LOAD HEIGHT | 59" |
| HEIGHT | 69" |
| WIDTH | 32" |
| DEPTH | 47" |
| WEIGHT: APPROX | 475 LBS. |

* Rates apply to material that has been properly conditioned.

ACCESSORY OPTIONS

| | |
|-------------------------|--------------------------|
| Wireless Remote Control | 3" x 150' Hose Package |
| 3" x 50' Blow Hose | 150' Remote Control Cord |
| 3" x 100' Hose Package | |

CERTAINTEED MACHINE WORKS

BOLT® 3 INSULATION BLOWING MACHINE

FEATURED DETAILS

QUAD AGITATION SYSTEM – An industry leading design composed of three rotating agitators and a patented spiked auger* that opens the compressed loosefill material, eliminates clumps, and prepares the material for further conditioning.

SEALED AIR-LOCK FEEDER – Sealed and pressurized air flow delivers a consistent flow of conditioned fiber.

BLOWER AIR CONTROL SYSTEM – Variable control of the air volume aids in fine tuning the air-to-material ratio.

MATERIAL CONTROL SLIDE – Adjustment of the fiber flow to the airlock feeder offers additional volume and conditioning control.

REMOTE CONTROL – Gives installer the option of selecting air only or air and fiber from the point of application.

POWDER-COAT FINISH – Durable, long-life protection for your investment.

INTEGRATED SAFETY FEATURES – Emergency stop switches; electrical interlock; front, rear and side guards.

SELF-ALIGNING SEALED BEARINGS – High quality, sealed bearings prevent dust intrusion, ensuring dependable and long-lasting operation.

Visit us at www.ctmchineworks.com
or call us at 800-237-7841 for more information.

*Patent nos. US8556200B2, US9592482B2, US10603672B2 and CA2726583C


CertainTeed Machine Works offers a comprehensive line of commercial and residential insulation and fireproofing application equipment, including blowing machines, vacuums and accessories. We provide equipment installation, troubleshooting and repair; custom machine design services; and same-day shipping of spare parts.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-237-7841 certainteeted.com

© 07/22 CertainTeed, Printed in the USA, 08-04-1128-US-EN



Standard Equipment

- (1) BOLT® 3 Machine
- (1) 100' Remote Control Cord
- (2) 50' Power Cords